

Multi zone inverter mini split

MODEL: CCD12KCHVS



Job Name:

Location:

Engineer Name:

File  Resubmit

Contractor:

System No:

Approval  Other

Date:

### General Features

- 2 Thermistor control
- 24-Hour on/off Timer
- Auto operation
- Auto restart
- Chaos swing
- Control lock function
- Drain Pump
- Inverter
- High And Low Pressure Protection Features
- Load Protection Features
- Over-Current Protection
- Anti Freeze Protection
- Wireless Remote control
- Optional Wired controller
- 4 Ways air distributor



### Unit Performance:

Nominal Cooling Capacity (Btu/h)	12 000
Nominal Heating Capacity (Btu/h)	13 000

\*\*\*\*

### Set Temperature

Cooling (°F WB)	61~86
Heating (°F DB)	61~86

### Piping

Liquid Line (in, OD)	1/4
Gas Line (in, OD)	3/8
Drain OD, ID (in)	1,57

### Electrical Specification

Power Supply	208-230V / 60Hz
Communications Wire Size	AWG 18
Rated Amps (A)	0,23

### Fan


Type	Centrifugal
Quantity	1
Motor/Drive	Direct Drive
Air Flow Rate (CFM)	353/294/265

### Unit Specification

Refrigerant Type	R410A
Refrigerant Control	EEV
Sound Pressure (dB(A))	46/44/42
Primary Filter	Yes
Net Weight (lbs)	39,6
Dehumidification (Pt/h)	2,96
Grill Dimension (in)	25.5x25.5x 1 7/8



### Outline Dimension Diagram



mm	Inch
650	25,59
570	22,44
400	15,74
604	23,77

### GLOSSARY

SEER - Seasonal Energy Efficiency Ratio

EER - Energy Efficiency Ratio

HSPF - Heating Seasonal Performance Factor

MOP - Maximum Overcurrent Protection

MCA - Minimum Circuit Ampacity



5965 Chemin de la Côte de Liesse  
Saint laurent, QC, Canada, H4T 1C3

Contact: +1 438 792 1956

[info@willishvac.com](mailto:info@willishvac.com)

[www.willishvac.com](http://www.willishvac.com)